



Think Packaging
Think "Navkar"

Pallet Stretch Wrapping Machine

Technical Specification



Suitable for Heavy Pallet, Doft start/stop, PLC Control,
Home Position, Sendor Pallet Height.

Technical Data	Description
Power Supply	1Phase, AC 220v, 50hz, 1 Kw (Anti Stretch)
Rotation Speed	0-10r/min(Optional)
Lifting Unit	Photoelectric switch controls the Height
Film-Stretching Unit	Film Tension Manually can be modified by Hand Grip (Mechnival Ani-Stretch) Film Tension Can Be Modified By Magnetic Brake (Magnetic Anti -Stretch)
Capacity	Turntable : 1500mm:1500 kg. / Turntable : > 1650mm:2000 kg. Maximum Package Weight 2000kg. > 2000kg. (custom -made is avaiable)
Column Height	Total Height of Column-2400 mm
Noise	75DB
Surrounding	Humidity ≤ 98%, Temperature-10°C ~ 40°C
Attachment	Turn Plate Diameter Φ1500 : L2440mm x W1500mm x H(2000~3400)mm (custom-made is available) Turn Plate Diameter Φ1650 : L2590mm x W1650mm x H(2000~3400)mm (custom-made is available)
Dimension of Machine	Turn Plate Diameter Φ1800 : L2740mm x W1800mm x H(2000~3400)mm (custom-made is available) Turn Plate Diameter Φ2000 : L2940mm x W2000mm x H(2000~3400)mm (custom-made is available) Turn Plate Diameter Φ2200 : L3140mm x W2200mm x H(2000~3400)mm (custom-made is available)
Film	LLDPE film, width ≤ 500mm, out diameter ≤ 280mm